


ZX80 FULLY RUGGED TABLET



- Qualcomm® QCS6490, Octa-core Processor
- 8" LumiBond display with Getac sunlight readable technology (1,000 nits) and glove-enabled capacitive touchscreen
- Hot-swappable battery design for uninterrupted operation in the field
- 6ft drop, MIL-STD-810H and IP67 certified
- Multiple configurations with enterprise-level management tools in a thin, light form factor
- Verified as Android enterprise recommended¹



SPECIFICATIONS

운영체제
Android™ 13.0

CPU (Mobile Computing Platform)
Qualcomm® QCS6490, Octa-core 1.9GHz
Max. 2.7GHz

그래픽 컨트롤러
Qualcomm® Adreno™ 643 GPU

NPU
Qualcomm® Hexagon™ Processor,
up to 13 TOPS with 6th Qualcomm AI Engine

디스플레이
8" Wide Viewing Angle TFT LCD WUXGA (1920 x 1200)
Protection film
1,000 nits LumiBond display with Getac sunlight readable
technology
Capacitive multi-touch screen

스토리지 & 메모리
12GB LPDDR5, 256GB UFS

키보드
Power button
3 tablet programmable buttons

포인팅 장치
Touchscreen
- Capacitive multi-touch screen
- 옵션: Dual mode touchscreen
(multi-touch and digitizer)

확장 슬롯
옵션: 1D/2D imager barcode reader
옵션: NFC ⁱⁱ

I/O 인터페이스
8M pixels webcam x 1
16M pixels auto focus rear camera x 1
Audio in/out combo x 1
USB 3.2 Gen 1 Type-C (with Display port & power delivery) x 1
MicroSD x 1 or Optional: Hybrid SIM card (Nano-SIM, 2FF)
tray with MicroSD x 1 ⁱⁱⁱ
Docking connector x 1
옵션: RF antenna pass-through for GPS,
WWAN and WLAN

통신 인터페이스
Wi-Fi 6E 802.11ax
Bluetooth (v5.2) ^{iv}
옵션: Dual SIM (Nano-SIM 2FF and e-SIM) ⁱⁱⁱ
옵션: 4G LTE mobile broadband ⁱⁱⁱ
옵션: 5G Sub-6 ⁱⁱⁱ
옵션: Dedicate GPS ^v

보안 기능
옵션: NFC ⁱⁱ

전원
Internal battery (3.86V, typical 4060mAh; min. 3950mAh)
LifeSupport battery swappable technology

Swappable Battery Options:
Battery bay cover (Default)
Battery (3.84V, typical 4990mAh; min. 4870mAh)
High capacity Li-ion battery
(3.84V, typical 9980mAh; min. 9470mAh)

치수 & 무게
234 x 149.8 x 17.6mm (9.21" x 5.89" x 0.69")
590g (1.3lbs) ^{vi}

견고성
MIL-STD-810H certified
IP67 certified
Vibration & 6ft (1.8m) drop resistant ^{vii}
옵션: ANSI/UL 121201, CSA C22.2 NO. 213
(Class I, Division 2, Groups A, B, C, D) ^{viii}

사용가능 환경
Temperature^{ix}:
- Operating: -29°C to 63°C / -20°F to 145°F
- Storage: -51°C to 71°C / -60°F to 160°F
Humidity:
- 95% RH, non-condensing

소프트웨어
Getac Camera
Getac Input Method
Getac Driving Safety Utility (trial version) agent/SDK
Getac settings and Google applications (Search, Chrome,
Gmail, Maps, YouTube, Play, Drive, YouTube music,
Google TV, Duo and photos)
Getac Log Tool
GDMS (trial version) agent/SDK

옵션:
Getac Driving Safety Utility
Getac OEMConfig

악세서리
옵션:
Carry bag
Battery (3.84V, typical 4990mAh; min. 4870mAh)
High capacity Li-ion battery
(3.84V, typical 9980mAh; min. 9470mAh)
DC-DC vehicle adapter (65W, 11-32VDC)
Multi-Bay charger (Dual-Bay)
Multi-Bay charger (Eight-Bay)
Digitizer pen with tether
Capacitive stylus with tether
Protection film
Hand strap with stylus holder
Rotating hand strap with kickstand
Shoulder strap (2-point)
Vehicle cradle ^x
Vehicle dock ^x
Office dock
65W USB-C AC Adapter

ZX80 FULLY
RUGGED TABLET

- I. Certified by June 2024. Android enterprise recommended rugged devices deliver a consistent set of features verified by Google with an elevated device baseline, increased security standards and enterprise-focused features and behaviors to meet the needs of users. Google and Android are trademarks of Google LLC.
- II. 13.56MHz contactless NFC (ISO 15693, 14443 A/B, Mifare and FeliCa™ compliant).
- III. One physical SIM card slot and one eSIM. Network service may vary depending on local telecommunication providers.
- IV. Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is operating in the area.
- V. Support GPS, GLONASS, Galileo and BeiDou.
- VI. Weight and dimensions vary from configurations and optional accessories.
- VII. Drop test results vary from configurations and optional accessories.
- VIII. Available with limited configurations and environment conditions.
- IX. Tested by an independent third-party test lab following MIL-STD-810H.
- X. Gamber-Johnson vehicle dock and cradle are e-mark certified.

Information provided herewith is for reference only, available specification shall be subjected to quotation by request.

	Vehicle Dock (Gamber-Johnson)	Vehicle Dock (RAM Mounts)
Serial Port	1	-
Audio In/Out Combo	-	-
DC in Jack	-	-
USB	USB 2.0 x 2	USB 2.0 x 2
LAN	1	1
HDMI	-	-
RF Antenna Connector	3 (option) (WWAN, WLAN, GPS)	-
Kensington Lock	-	-



(주)씨에스글로비즈
경기도 과천시 과천대로7길 65, 과천상상자이타워 B동 1220호
제품 문의 : 02)782-4700 / 기술 문의 : 02)782-7500
www.getac.co.kr / getac_sales@getac.co.kr