


X600 FULLY RUGGED LAPTOP



- 11th Generation Intel® Core™ i7 / i5 vPro® Processor
- 15.6" FHD LumiBond display with Getac sunlight readable technology (1,000 nits) and optional capacitive touchscreen
- Enhanced enterprise security features with TPM 2.0, Kensington lock, triple user-replaceable storage and Smart card reader
- Versatile I/Os connectivity including Thunderbolt™ 4 and docking solutions
- Dual batteries with the hot-swappable capability
- Optional discrete graphic NVIDIA® Quadro® RTX3000



X600 3D demo



SPECIFICATIONS

운영 체제

Windows 11 Pro

CPU

Intel® Core™ i5-11500HE vPro® Processor
Max. 4.5GHz with Intel® Turbo Boost Technology
- 12MB Intel® Smart Cache

Platform options:

Intel® Core™ i7-11850HE vPro® Processor
Max. 4.7GHz with Intel® Turbo Boost Technology
- 24MB Intel® Smart Cache

Intel® Xeon® W-11865MRE vPro® Processor
Max. 4.7GHz with Intel® Turbo Boost Technology
- 24MB Intel® Smart Cache

그래픽 컨트롤러

Intel® UHD Graphics
옵션: NVIDIA® Quadro® RTX3000
6GB discrete graphics controller^{i,ii,iii}
옵션: NVIDIA® GeForce® GTX1650
4GB discrete graphics controller^{i,ii}
옵션: NVIDIA® RTX™ A4500
16GB discrete graphics controller^{i,ii,iii}

디스플레이

15.6" TFT LCD FHD (1920 x 1080)
Protection film
1,000 nits LumiBond display with Getac sunlight readable technology
옵션: Capacitive multi-touch screen

스토리지 & 메모리

16GB DDR4
옵션: 32GB / 64GB / 128GB DDR4

512GB PCIe SSD
옵션: 1TB / 2TB PCIe SSD
옵션 2nd storage: 512GB / 1TB / 2TB PCIe SSD
옵션 3rd storage: 512GB / 1TB / 2TB PCIe SSD

키보드

LED backlit membrane keyboard
with integrated numeric keypad

포인팅 장치

Touchscreen
- 옵션: Capacitive multi-touch screen
Touchpad
- Touchpad with two buttons

오디오

Integrated stereo speakers
Integrated dual-array microphone

확장 슬롯

Smart card reader
옵션: ExpressCard 54 or PCMCIA Type II^{iv}
옵션: SD card reader

I/O 인터페이스

5MP webcam x 1
Thunderbolt™ 4 Type-C x 1^{xviii}
USB 3.2 Gen 2 Type-A x 4
LAN (RJ-45) x 2
Audio in/out combo x 1
DC in Jack x 1
HDMI 2.0 x 1
Display port x 1
Docking connector x 1
Serial port (9-pin; D-sub) x 1
External VGA (15-pin; D-sub) x1 or 2nd
serial port (9-pin; D-sub) x 1^v
옵션: SIM card slot x 1 (Mini-SIM, 2FF)^{vi}
옵션: RF antenna pass-through for GPS,
WWAN and WLAN

통신 인터페이스

2.5GBASE-T Ethernet
Intel® Wi-Fi 6E AX210, 802.11ax
Bluetooth (v5.2)^{vii}
옵션: Dedicated GPS with L1/L5^{viii,ix}
옵션: 4G LTE mobile broadband with
integrated GPS^{xv,xviii}

보안 기능

TPM 2.0
Kensington lock
Smart card reader
Intel® vPro® Technology
Getac Disk Wipe
옵션: Absolute Persistence®

전원

AC adapter (150W, 100-240VAC, 50/60Hz)ⁱⁱ
AC adapter (230W, 100-240VAC, 50/60Hz)ⁱ
Battery (10.8V, typical 6900mAh; min. 6600mAh) x 2

치수 & 무게

412 x 322 x 52.5mm (16.22" x 12.68" x 2.07")^x
4.41kg (9.72lbs)^x

견고성

MIL-STD-810H certified
IP66 certified
MIL-STD-461G certified^{xi}
Vibration and 4ft (1.2m) drop resistant
옵션: ANSI/UL 121201, CSA C22.2 NO. 213
(Class I, Division 2, Groups A, B, C, D)
옵션: Salt fog certified

사용가능 환경

Temperature^{xii} :
- Operating: -29°C to 63°C / -20°F to 145°F
- Storage: -51°C to 71°C / -60°F to 160°F
Humidity:
- 95% RH, non-condensing

소프트웨어

Getac Utility
Getac Geolocation
옵션: Absolute Secure Endpoint
옵션: Absolute Secure Access

옵션:

Getac VGPS Utility

악세서리

Battery (10.8V, typical 6900mAh; min. 6600mAh) x 2
AC adapter (150W, 100-240VAC, 50/60Hz)ⁱⁱ
or AC adapter (230W, 100-240VAC, 50/60Hz)ⁱ
Capacitive stylus with tether

옵션:

Backpack
Battery (10.8V, typical 6900mAh; min. 6600mAh)
Multi-Bay charger (Dual-Bay)
AC adapter (150W, 100-240VAC, 50/60Hz)ⁱⁱ
AC adapter (230W, 100-240VAC, 50/60Hz)ⁱ
Office dock AC adapter (230W, 100-240VAC, 50/60Hz)ⁱ
MIL-STD-461 AC adapter (230W, 100-240VAC)^x
DC-DC vehicle adapter (230W, 11-32VDC)
Capacitive stylus with tether
Protection film
Vehicle dock
Office dockⁱⁱ
Spare SSD kit

X600 FULLY RUGGED LAPTOP

- I. The configuration with a discrete graphic controller requires the 230W AC adapter.
- II. 150W AC adaptor is not applicable with discrete graphic controller nor office dock.
- III. For X600 optional NVIDIA® Quadro® RTX3000, the operating temperature is 0°C to 63°C / 32°F to 145°F.
- IV. ExpressCard 54 and PCMCIA Type II card readers are mutually exclusive.
- V. The 2nd serial port is optional and mutually exclusive with External VGA.
- VI. Units with 4G LTE option comes with an embedded SIM card slot.
- VII. Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is operating in the area.
- VIII. Dedicated GPS and 4G LTE are mutually exclusive options.
- IX. Support GPS, GLONASS, Galileo, BeiDou and QZSS.
- X. Weight and dimensions vary from configurations and optional accessories.
- XI. MIL-STD-461 230W AC adapter sold separately.
- XII. Tested by an independent third-party test lab following MIL-STD-810H.
- XIII. Does not support USB power delivery.

Information provided herewith is for reference only, available specification shall be subjected to quotation by request.

	Office Dock	Vehicle Dock
Serial Port	1	2
External VGA	1	1
Microphone	1	-
Audio Output	1	-
DC in Jack	1	1
USB	5	6
LAN	2	2
HDMI	1	1
Display port	1	1
RF Antenna Connector	-	1 (GPS, WWAN, WLAN)
Kensintonlock	1	1



(주)씨에스글로벌비즈

경기도 과천시 과천대로7길 65, 과천상상자이타워 B동 1220호

제품 문의 : 02)782-4700 / 기술 문의 : 02)782-7500

www.getac.co.kr / getac_sales@getac.co.kr