




X600 Pro-PCI FULLY RUGGED LAPTOP

- 11th Generation Intel® Core™ i7 / i5 vPro® Processor
- 15.6" FHD LumiBond display with Getac sunlight readable technology (1,000 nits) and optional capacitive touchscreen
- Enhanced enterprise security features with TPM 2.0, Kensington lock, triple user-replaceable storage and Smart card reader
- Versatile I/Os connectivity including Thunderbolt™ 4 and docking solutions
- Four batteries with the hot-swappable capability



X600 Pro-PCI 3D demo



SPECIFICATIONS

운영 체제
Windows 11 Pro
CPU
Intel® Core™ i5-11500HE vPro® Processor
Max. 4.5GHz with Intel® Turbo Boost Technology
- 12MB Intel® Smart Cache

Platform options:
Intel® Core™ i7-11850HE vPro® Processor
Max. 4.7GHz with Intel® Turbo Boost Technology
- 24MB Intel® Smart Cache

Intel® Xeon® W-11865MRE vPro® Processor
Max. 4.7GHz with Intel® Turbo Boost Technology
- 24 MB Intel® Smart Cache

그래픽 컨트롤러
Intel® UHD Graphics
옵션: NVIDIA® GeForce®
GTX1650 4GB discrete graphics controller^{i, ii}

디스플레이
15.6" TFT LCD FHD (1920 x 1080)
Protection film
1,000 nits LumiBond display with
Getac sunlight readable technology
옵션: Capacitive multi-touch screen

스토리지 & 메모리
16GB DDR4
옵션: 32GB / 64GB / 128GB DDR4

512GB PCIe SSD
옵션: 1TB / 2TB PCIe SSD
옵션 2nd storage: 512GB / 1TB / 2TB PCIe SSD
옵션 3rd storage: 512GB / 1TB / 2TB PCIe SSD

키보드
LED backlit membrane keyboard
with integrated numeric keypad
포인팅 장치
Touchscreen
- 옵션: Capacitive multi-touch screen touchpad
- Touchpad with two buttons

오디오
Integrated stereo speakers
Integrated dual-array microphone

확장 슬롯
Smart card reader
ExpressCard 54 + PCMCIA Type II
PCI or PCI-Express 3.0 expansion unit
(x2 slots)^{iii, iv, v}
옵션: 2nd ExpressCard 54 or 2nd
PCMCIA Type II^{vi}
옵션: SD card reader

Multimedia Bay
DVD super multi drive^{vii}
옵션: Blu-Ray super multi drive^{vii}

I/O 인터페이스
5MP webcam x 1
Thunderbolt™ 4 Type-C x 1^{xvi}
USB 3.2 Gen 2 Type-A x 4
LAN (RJ-45) x 2
Audio in/out combo x 1
DC in Jack x 1
HDMI 2.0 x 1
Display port x 1
Serial port (9-pin; D-sub) x 2
External VGA (15-pin; D-sub) x1
or 3rd serial port (9-pin; D-sub) x 1^{viii}
옵션: SIM card slot x 1 (Mini-SIM, 2FF)^{ix}

통신 인터페이스
2.5GBASE-T Ethernet
Intel® Wi-Fi 6E AX210, 802.11ax
Bluetooth (v5.2)^x
옵션: Dedicated GPS^{xi}
옵션: 4G LTE mobile broadband
with integrated GPS^{ix, xi}

보안 기능
TPM 2.0
Kensington lock
Smart card reader
Intel® vPro® Technology
Getac Disk Wipe
옵션: Absolute Persistence®

전원
AC adapter (230W, 100-240VAC, 50/60Hz)
Battery (10.8V, typical 6900mAh;
min. 6600mAh) x 4

치수 & 무게
412 x 322 x 108.8mm (16.22" x 12.68" x 4.28")^{xii}
8.145kg (17.95 lbs)^{xii}

견고성
MIL-STD-810H certified
IP66 certified
MIL-STD-461G certified^{xi}
Vibration and 3ft (0.9m) drop resistant

사용가능 환경
Temperature^{xv} :
- Operating: -29°C to 63°C / -20°F to 145°F
- Storage: -51°C to 71°C / -60°F to 160°F
Humidity:
- 95% RH, non-condensing

소프트웨어
Getac Utility
Getac Geolocation
옵션: Absolute Secure Endpoint
옵션: Absolute Secure Access

옵션:
Getac Device Monitoring System (GDMS)

악세서리
Battery (10.8V, typical 6900mAh; min. 6600mAh) x 4
AC adapter (230W, 100-240VAC, 50/60Hz)
Capacitive stylus with tether

옵션:
Backpack
Battery (10.8V, typical 6900mAh; min. 6600mAh)
Multi-Bay charger (Dual-Bay)
Multimedia bay DVD super multi drive^{vii}
Multimedia bay Blu-Ray super multi drive^{vii}
AC adapter (230W, 100-240VAC, 50/60Hz)
MIL-STD-461 AC adapter (230W, 100-240VAC)^{xiii}
DC-DC vehicle adapter (230W, 11-32VDC)
Capacitive stylus with tether
Protection film
Spare SSD kit

X600 Pro-PCI
FULLY RUGGED
LAPTOP

- I. The configuration with a discrete graphic controller requires the 230W AC adapter.
- II. 150W AC adaptor is not applicable with discrete graphic controller nor office dock.
- III. PCI or PCI-Express expansion unit is not compatible with vehicle dock nor office dock.
- IV. The PCI or PCI-Express expansion unit is not compatible with NVIDIA® Quadro RTX3000.
- V. PCI and PCI-E slots are mutually exclusive options.
- VI. The 2nd ExpressCard 54 and the 2nd PCMCIA Type II card readers are mutually exclusive.
- VII. DVD super multi drive and Blu-Ray super multi drive are mutually exclusive.
- VIII. The 3rd Serial port is optional and mutually exclusive with External VGA.
- IX. Units with 4G LTE option comes with an embedded SIM card slot.
- X. Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is operating in the area.
- XI. Dedicated GPS and 4G LTE are mutually exclusive options.
- XII. Weight and dimensions vary from configurations and optional accessories.
- XIII. MIL-STD-461 230W AC adapter sold separately.
- XIV. X600 Pro-PCI can withstand 3ft (0.9m) drop in packaging.
- XV. Tested by an independent third-party test lab following MIL-STD-810H.
- XVI. Does not support USB power delivery.

Information provided herewith is for reference only, available specification shall be subjected to quotation by request.



(주)씨에스글로비즈
경기도 과천시 과천대로7길 65, 과천상상자이타워 B동 1220호
제품 문의 : 02)782-4700 / 기술 문의 : 02)782-7500
www.getac.co.kr / getac_sales@getac.co.kr